

# POWERED SUBWOOFER GENERAL INFORMATION INDEX

Copyright © Audioholics.com / Josh Ricci 2015

MANUFACTURER & MODEL	RETAIL PRICE	MANUFACTURER'S WARRANTY	DIMENSIONS LxWxH (inches)	EXTERNAL VOLUME (cubic feet) / (liters)	WEIGHT (lbs) / (kilograms)	DRIVER CONFIG	AMPLIFIER POWER RATING	SYSTEM TYPE	MULTIPLE MODES?	BUILT IN PEQ?
<a href="#">APERION: BRAVUS II 12D</a>	\$899	10 years / 2 electronics	15.5x15.5x17	2.36 / 67.3	62 / 28.1	1x12"	650w	reflex (PR's)	NO	NO
<a href="#">B&amp;W: ASW-610XP</a>	\$1,199	5 years / 2 electronics	14.8x12.8x12.8	1.4 / 39.6	34.4 / 15.6	1x10"	500w	sealed	NO	YES
<a href="#">BIC ACOUSTECH: PL-200</a>	\$279	8 years / 2 electronics	19.5x14.75x17.25	2.88 / 81.6	47 / 21.3	1x12"	250w	bass reflex	NO	NO
<a href="#">CADENCE CSX-15 MKII</a>	\$499	2 years	18x19x21.5	4.26 / 120	88 / 40	1x15"	300w	bass reflex	NO	NO
<a href="#">ELEMENTAL DESIGNS: A7S-450</a>	\$849	1 year	23.5x22.25x22.75	6.88 / 195	130 / 59	1x18"	1300w	sealed	NO	NO
<a href="#">EMOTIVA: X-REF12</a>	\$599	5 years	15.5x14.625x15.625	2.05 / 58.5	44 / 20	1X12"	600w	sealed	NO	YES
<a href="#">EPIK SUBWOOFERS: EMPIRE</a>	\$799	3 years	24x18x22	5.5 / 156	125 / 56.7	2x15"	600w	sealed	NO	NO
<a href="#">FUNK AUDIO FW18.0</a>	\$3,234	3 years	20.5x22x22	5.7/ 164	95 / 43	1X18"	2400W	sealed	NO	YES
<a href="#">HSU: VTF-15H</a>	\$879	7 years / 2 electronics	25x18x26	6.8/191.7	120 / 54	1x15"	350w	ported	YES	NO
<a href="#">JL AUDIO: E110</a>	\$1,500	3 years	16.5x13.5x14.25	1.84 / 52	52.7	1x10"	1200w	sealed	NO	NO
<a href="#">JL AUDIO: E112</a>	\$1,900	3 years	18.4x15.5x16.25	2.68 / 75.8	73.5	1x12"	1500w	sealed	NO	NO
<a href="#">KLIPSCH: SW-311</a>	\$1,599	2 years	16.25x13x13.4375	1.64 / 46.4	37 / 16.8	1x10"	500w	reflex (PR's)	NO	YES
<a href="#">MARTIN LOGAN DYNAMO 1500X</a>	\$1,595	3 years	18.3x16.75x17.6	3.125 / 90	52 / 23.6	1x15"	650w	sealed	NO	NO
<a href="#">OUTLAW AUDIO: LFM-1 EX</a>	\$649	3 years	24x17x22.75	5.31 / 150	80 / 36.3	1x12"	350w	bass reflex	YES	NO
<a href="#">PARADIGM SIGNATURE SUB 2</a>	\$8,999	5 years / 3 electronics	22.375x23.75x24.5	7.5 / 214	230 / 104.3	6x10"	4500w	sealed	NO	YES
<a href="#">POWERSOUND: XV-15</a>	\$799	5 years	23.5x18.5x24.25	6.1 / 174	92 / 42	1x15"	500w	bass reflex	NO	NO
<a href="#">PREMIER ACOUSTICS: PA-150</a>	\$349	5 years / 2 electronics	19x18x21	4.2 / 119	69 / 31.3	1x15"	250w	bass reflex	NO	NO
<a href="#">RBH SOUND: SX-12</a>	\$1,099	5 years / 1 electronics	21.125x17.7x19.625	4.25 / 120	53 / 24	1x12"	350w	bass reflex	NO	NO
<a href="#">RBH SOUND: SX-1212R</a>	\$5,300	5 years / 1 electronics	17.75x38.5x21	8.3 / 237	130 / 59	2x12"	2400w	bass reflex	NO	NO
<a href="#">RYTHMIK AUDIO: FV15HP</a>	\$1,199	5 years / 2 electronics	26x18x24	6.5 / 184	110 / 49.9	1x15"	600w	bass reflex	YES	YES
<a href="#">SVS: PB12-NSD</a>	\$769	5 years	22x17.3x20.9	4.6 / 131	66 / 30	1x12"	400w	bass reflex	NO	NO
<a href="#">SVS: PB13-ULTRA SLEDGE DSP</a>	\$1,999	5 years	29.25x20.5x22.5	7.8 / 221	155 / 70.3	1x13.5"	1000w	reflex / seal	YES	YES
<a href="#">SVS: SB12-NSD</a>	\$649	5 years	14.2x14.2x14.6	1.7 / 48.5	35 / 16	1x12"	400w	sealed	NO	NO
<a href="#">SVS: SB13-ULTRA</a>	\$1,599	5 years	17.4x17.4x17.4	3.1 / 87	92 / 42	1x13.5"	1000w	sealed	NO	YES
<a href="#">VELODYNE: DD18+</a>	\$4,999	2 years	25.6x20.67x22.72	6.9 / 197	142 / 64.4	1X18"	1250w	sealed	NO	YES
<a href="#">VELODYNE: EQ-MAX 15</a>	\$879	2 years	21x19x21.5	5 / 142	75 / 34	1x15"	750w	bass reflex	NO	YES
<a href="#">XTZ Sound 3X12</a>	\$2,499	5 years / 2 electronics	21.9x21.1x44.5	11.9 / 337	170.3 / 77.3	3x12"	1500w	reflex / seal	YES	NO

Latest Version: August 31st, 2015

# CEA2010 MAX CLEAN RMS SUBWOOFER OUTPUT

ALL DATA COLLECTED OUTDOORS / GROUND PLANE AND REFERENCED TO 2 METER RMS dB SPL VALUES

Copyright © Audioholics.com / Josh Ricci 2015

MANUFACTURER & MODEL	CEA2010 CENTER FREQUENCY												BANDWIDTH UNIFORMITY	FREQUENCY RANGE
	10hz	12.5hz	16hz	20hz	25hz	31.5hz	40hz	50hz	63hz	80hz	100hz	125hz	20-80Hz	+/-3dB Window
APERION: BRAVUS II 12D	/	/	/	87.0	100.2	105.3	109.8	112.6	112.2	110.7	109.8	109.3	+/-12.8dB	40-125Hz
B&W: ASW-610XP	/	/	/	85.1	90.0	96.1	101.5	105.9	108.9	108.1	106.2	104.9	+/-11.9dB	50-125Hz
BIC ACOUSTECH: PL-200	/	/	/	84	96.2	102.5	107.7	110.4	108.1	106.5	105.3	103.8	+/-13.2dB	40-100Hz
CADENCE CSX-15 MKII	/	/	/	83.8	89.7	93.3	98.6	109.3	115.5	120.2	119.3	116.8	+/-18.2dB	63-125Hz
ELEMENTAL DESIGNS: A7S-450	/	90	94.6	100.4	106.8	112.5	117.8	121	120.1	118.3	116.8	115.8	+/-10.3dB	40-125Hz
EMOTIVA: X-REF12	/	/	/	81.0	89.5	99.1	103.5	107.6	108.5	107.7	106.3	105.1	+/-13.8dB	40-125Hz
EPIK: EMPIRE	/	93.5	98.2	102.2	105.8	109.7	113.2	116.4	119.2	121.6	123.3	124.2	+/-9.7dB	63-125Hz
FUNK AUDIO: 18.0	91.9	95.5	99.2	103.6	108.8	114.9	119.9	121.4	121.9	121.7	121.6	121.6	+/-9.2dB	40-125Hz
HSU: VTF-15H: SEALED, EQ1	/	88.2	92.4	96.9	102.6	109.4	111.5	112.3	113.3	114.2	114.7	115.4	+/-8.7dB	31.5-125Hz
HSU: VTF-15H: 1 PORT OPEN, EQ1	/	93.5	100.6	104.1	106.9	111.3	113.5	113.7	114.2	114.6	115.1	115.5	+/-5.3dB	31.5-125Hz
HSU: VTF-15H: 2 PORTS OPEN, EQ2	/	/	93.4	104.1	109.7	113.1	115.6	115.3	115.3	115.5	115.6	115.9	+/-5.7dB	25-100Hz
JL AUDIO: E110	/	/	89.1	93.3	98.6	104.2	108.7	112.2	113.4	113	111.8	111.2	+/-10dB	40-125Hz
JL AUDIO: E112	/	87.7	92.6	97.5	103.2	108.6	112.4	114.7	115	113.7	112.5	111.5	+/-8.8dB	40-125Hz
KLIPSCH: SW-311	/	/	/	84.2	97.9	102.6	105.3	108.6	111.4	112.2	111.5	110.6	+/-14dB	50-125Hz
MARTIN LOGAN: DYNAMO 1500X	/	89.9	92.6	97.4	101.4	105.3	110.0	114.1	115.3	114.4	113.2	112.1	+/-9dB	40-125Hz
OUTLAW AUDIO: LFM-1 EX: 18hz	/	/	97.5	102.1	104.7	107.2	110.5	112.4	113.3	113.3	112.9	112.8	+/-5.6dB	31.5-125Hz
OUTLAW AUDIO: LFM-1 EX: 25hz	/	/	86.9	101.0	107.3	110.7	112.3	113.7	113.8	113.7	113.1	112.8	+/-6.4dB	31.5-125Hz
PARADIGM SIGNATURE SUB 2	94.7	98.2	102.6	106.4	109.9	113.2	116.9	120.2	122.5	123.0	122.1	120.3	+/-8.3dB	40-125Hz
POWERSOUND: XV-15	/	/	98.1	102.7	106.2	109.6	113.7	116.6	114.7	112.5	110.8	109.3	+/-7dB	40-100Hz
PREMIER ACOUSTICS: PA-150	/	/	/	93.6	98.6	105.4	109.3	114.4	118.0	117.8	116.9	116.0	+/-12.2dB	50-125Hz
RBH SOUND: SX-12	/	/	/	87.7	98.0	108.0	111.1	113.7	112.7	112.1	111.7	111.6	+/-13dB	31.5-125Hz
RBH SOUND: SX-1212R	/	99.6	107.7	112.8	114.5	117.3	120.8	120.1	120.5	120.6	120.6	120.7	+/-4dB	31.5-125Hz
RYTHMIK AUDIO: FV15HP: 1 PORT MODE	/	98.5	104.0	108.3	111.7	115.3	117.8	118.0	117.9	117.8	117.6	117.2	+/-4.9dB	31.5-125Hz
RYTHMIK AUDIO: FV15HP: 2 PORTS MODE	/	89.8	102.1	108.1	113.1	117.0	119.5	119.1	118.8	118.4	118.2	118.1	+/-5.7dB	31.5-125Hz
SVS PB12-NSD	/	/	93.3	103.2	105.0	105.9	106.5	107.3	108.0	108.7	109.2	109.6	+/-2.8dB	20-100Hz
SVS SB12-NSD	/	81.1	87.7	91.9	96.3	101.0	104.6	106.4	107.6	108.2	108.5	108.5	+/-8.2dB	40-125Hz
SVS SB13-ULTRA	83	88.6	92.6	96.5	101.3	108.1	112.1	114.9	116.8	117.3	117.2	116.9	+/-10.4dB	40-125Hz
SVS: PB13-ULTRA: 15HZ MODE	/	89.3	105.1	109.2	111.1	113.6	116.4	116.7	115.9	114.8	113.8	113.4	+/-3.8dB	25-125Hz
SVS: PB13-ULTRA: 20HZ MODE	/	/	97.4	110.6	113.5	115.5	117.5	117.8	116.6	115.3	114.4	114.1	+/-3.6dB	25-125Hz
SVS: PB13-ULTRA: SEALED MODE	/	84.6	91.5	97.6	104.0	110.0	113.8	115.2	114.7	114.0	113.4	113.0	+/-8.8dB	31.5-125Hz
VELODYNE EQ-MAX 15	/	/	/	84.8	95.7	104.2	110.0	114.2	114.8	111.0	108.3	106.7	+/-15dB	40-80Hz
VELODYNE: DD18+ SERVO GAIN 1	84.6	89.2	98.8	103.4	108.3	113.0	115.8	116.8	115.3	113.5	112.1	110.5	+/-6.7dB	31.5-125Hz
VELODYNE: DD18+ SERVO GAIN 8	86.1	92.5	98.9	103.6	108.2	112.9	115.3	116.3	115.1	113.4	112.0	110.6	+/-6.4dB	31.5-125Hz
XTZ SOUND 3X12	/	97.0	106.1	111.5	115.5	118.8	121.8	122.4	122.4	122.6	123.1	123.4	+/-5.6dB	31.5-125Hz
<b>HIGHEST RECORDED VALUE</b>														

Tested by Paul Apollonio (Funk and SVS) and Joel Foust (RBH models)

MANUFACTURER & MODEL	CEA2010 CENTER FREQUENCY												BANDWIDTH UNIFORMITY	FREQUENCY RANGE
	10hz	12.5hz	16hz	20hz	25hz	31.5hz	40hz	50hz	63hz	80hz	100hz	125hz	20-60Hz	+/-3dB Window
Funkywaves: FW 12.X	/	/	/	107.0	112.3	112.4	114.0	113.9	113.1	/	/	/	+/-3.5dB	25-63Hz
RBH: SX-10R	/	/	/	/	94.0	103.0	106.0	108.0	109.0	108.0	107.0	105.0	+/-3.5dB	25-63Hz
RBH: S-10	/	/	/	/	/	98	105	107	107	106	105	103	+/-4.2dB	25-63Hz
SVS: PB12-Plus DSP	/	/	/	107	109.5	111.5	114.3	115.3	115.3	/	/	/	+/-4.2dB	25-63Hz

# MAX RMS SUBWOOFER OUTPUT RECORDED VIA LONG DURATION SINE SWEEP

ALL DATA COLLECTED OUTDOORS / GROUND PLANE AND REFERENCED TO 2 METER RMS dB SPL VALUES

Copyright © Audioholics.com / Josh Ricci 2015

MANUFACTURER & MODEL	FREQUENCY												BANDWIDTH UNIFORMITY	FREQUENCY RANGE
	10Hz	12.5Hz	16Hz	20Hz	25Hz	31.5Hz	40Hz	50Hz	63Hz	80Hz	100Hz	125Hz		
APERION: BRAVUS II 12D	/	/	83.2	90.1	97.4	102.1	103.7	104.6	101.6	101.9	102.0	101.8	+/-7.3dB	31.5-125Hz
B&W: ASW-610XP	/	80.8	86.1	88.8	92.8	96.7	100.7	104.1	105.7	104	103.6	101.3	+/-8.4dB	38-125Hz
BIC ACOUSTECH: PL-200	/	/	82.1	87.1	95.1	101.9	106.3	107.6	103.7	101.9	100.8	97.8	+/-10.2dB	36-63Hz
CADENCE CSX-15 MKII	/	/	/	88.5	92.4	96.5	101.8	106.8	113.3	119.0	116.0	113.4	+/-15.3dB	63-125Hz
ELEMENTAL DESIGNS: A7S-450	84	91.2	98.9	102.9	107.0	111.9	116.8	119.6	117.9	115.9	114.4	114.3	+/-8.3dB	35-125Hz
EMOTIVA: X-REF12	/	/	/	83.3	94.3	99.7	103.4	104.6	104.0	101.2	99.6	97.2	+/-10.6dB	29-106Hz
EPIK: EMPIRE	80	88.1	98.6	102.1	106.0	109.3	110.8	112.7	115.1	117.3	118.2	119.4	+/-7.6dB	55-125Hz
FUNK AUDIO 18.0	91.3	95.1	98.2	103.1	108.0	114.1	119.7	121.0	118.3	117.3	116.9	116.8	+/-9.0dB	33.5-125Hz
HSU: VTF-15H: SEALED, EQ1	82.6	90.2	95.5	99.7	104.3	109.4	110.7	111.6	111.1	112.6	112.4	112.5	+/-6.5dB	28.5-125Hz
HSU: VTF-15H: 1 PORT OPEN, EQ1	84.4	93.1	100.7	104.4	107.1	111.0	112.9	113.3	112.4	113.5	113.1	113.1	+/-4.6dB	26.5-125Hz
HSU: VTF-15H: 2 PORTS OPEN, EQ2	/	83	95	102.0	109.4	112.8	115.5	115.0	113.2	114.1	113.6	113.2	+/-6.8dB	26-125Hz
JL AUDIO: E110	78.7	85.4	89.8	93.3	97.8	102.4	107.2	109.0	106.8	106.8	105.5	104.7	+/-7.9dB	34-125Hz
JL AUDIO: E112	81.9	88.9	94.1	97.5	101.9	106.8	108.8	108.0	106.6	107.2	106.9	105.4	+/-5.7dB	27.5-125Hz
KLIPSCH: SW-311	/	/	/	73.1	93.9	99.8	101.8	103.9	106.7	108.0	109.3	107.5	+/-17.4dB	45-125Hz
MARTIN LOGAN DYNAMO 1500X	81.9	87.6	92.6	96.3	100.7	105.4	109.8	114.5	113.1	111.9	110.8	110.3	+/-9.1dB	36-125Hz
OUTLAW AUDIO: LFM-1 EX: 18hz	/	85.4	97	101.8	103.0	104.7	107.7	109.8	111.3	110.5	110.0	108.3	+/-4.7dB	35-125Hz
OUTLAW AUDIO: LFM-1 EX: 25hz	/	/	89	99.5	106.5	109.2	110.6	111.8	112.1	111.1	111.0	109.4	+/-6.3dB	25-125Hz
PARADIGM SIGNATURE SUB 2	96.3	99.1	102.9	105	106.9	109.1	110.6	111.6	111.6	112	112.5	112.2	+/-3.5dB	24-125Hz
POWERSOUND: XV-15	82.3	92.2	98.5	101.4	103.7	106.4	109.2	111.5	111.2	110.2	107.8	106.8	+/-5.1dB	31.5-125Hz
PREMIER ACOUSTICS: PA-150	/	81.1	90.2	95.2	99.4	103.4	107.3	112.1	116.0	114.9	113.5	113.4	+/-10.4dB	45-125Hz
RBH SOUND: SX-12	/	/	81.6	91.1	98.7	105.8	109.2	110.8	109.8	108.6	108.4	107.1	+/-9.8dB	31-125Hz
RBH SOUND: SX-1212R	83.4	94.5	106.5	111.3	114.3	116.1	116.7	116.5	115.8	115.6	114.4	113.8	+/-3dB	20-125Hz
RYTHMIK AUDIO: FV15HP: 1 PORT MODE	89	97.8	104	107.6	110.8	112.4	112.6	113.4	113.0	111.0	107.3	105.3	+/-2.9dB	20-100Hz
RYTHMIK AUDIO: FV15HP: 2 PORTS MODE	/	85.5	100.9	106.9	112.1	114.7	114.8	115.9	115.6	113.8	110.3	108.7	+/-4.5dB	22.5-105Hz
SVS PB12-NSD	/	/	91	99.4	104.3	105.2	105.3	106.2	106.8	107.2	107.5	108.2	+/-3.9dB	22-125Hz
SVS SB12-NSD	/	79.4	87.3	92.0	96.3	100.0	103.5	105.4	107.1	107.6	107.6	107.3	+/-7.8dB	37-125Hz
SVS SB13-ULTRA	86.9	90.3	94.4	97.8	101.1	105.1	108.4	111.7	113.0	113.6	112.2	111.4	+/-8dB	36.5-125Hz
SVS: PB13-ULTRA: 15HZ MODE	79.8	92.5	104.8	107.9	109.4	112.2	114.8	113.3	112.9	111.0	110.1	108.6	+/-3.4dB	23-125Hz
SVS: PB13-ULTRA: 20HZ MODE	/	85.9	99.5	109.3	111.9	113.4	115.9	115.1	113.3	111.2	110.2	109.0	+/-3.3dB	21-100Hz
SVS: PB13-ULTRA: SEALED MODE	86.8	91.4	96.4	100.2	104.6	109.5	112.4	111.1	111.4	109.9	109.2	107.8	+/-6.1dB	28-125Hz
VELODYNE EQ-MAX 15	/	/	78.8	91.7	98.1	102.8	107.8	112.4	111.8	107.9	105.7	104.7	+/-10.3dB	38-86Hz
VELODYNE: DD18+ SERVO GAIN 1	88.3	94.6	99.5	103.3	107.8	113.0	116.1	113.6	110.8	108.7	107.4	104.8	+/-6.4dB	28-63Hz
VELODYNE: DD18+ SERVO GAIN 8	88.3	93.5	99.1	102.8	107.3	111.6	113.6	114.1	112.9	111.7	111.0	109.8	+/-5.6dB	28-125Hz
XTZ SOUND 3X12	70.7	92	101.5	107.6	112.7	116.3	118.5	118.6	118.2	118.3	118.0	118.2	+/-6.4dB	28-63Hz

# AUDIOHOLICS "BASSAHOLIC" SUBWOOFER RATINGS

MAXIMUM SUGGESTED ROOM SIZE TO ENSURE ADEQUATE OUTPUT HEADROOM

Copyright © Audioholics.com / Josh Ricci 2015

MANUFACTURER & MODEL	MINIMUM PASSING CRITERIA BASED ON CEA2010 2 METER GROUNDPLANE PEAK OUTPUT CONVERTED TO 4 METER 1/8TH SPACE				
	31.5-63Hz SPL	<109db	>109db	115db	123db
25Hz SPL ROOM SIZE	<103db	>103db	109db	117db	
	SMALL	MEDIUM	LARGE	EXTREME	
	<1500cu ft	1500-3000cu ft	3000-5000cu ft	>5000cu ft	
APERION: BRAVUS II 12D			CERTIFIED		
B&W: ASW-610XP	CERTIFIED				
BIC ACOUSTECH: PL-200		CERTIFIED			
CADENCE CSX-15 MKII	CERTIFIED				
ELEMENTAL DESIGNS: A7S-450			CERTIFIED		
EMOTIVA: X-REF12	CERTIFIED				
EPIK: EMPIRE			CERTIFIED		
FUNK AUDIO: 18.0				CERTIFIED	
HSU: VTF-15H SEALED, EQ1			CERTIFIED		
HSU: VTF-15H 1 PORTS, EQ1			CERTIFIED		
HSU: VTF-15H 2 PORTS, EQ2				CERTIFIED	
JL AUDIO: E110		CERTIFIED			
JL AUDIO: E112			CERTIFIED		
KLIPSCH: SW-311		CERTIFIED			
MARTIN LOGAN: DYNAMO 1500X			CERTIFIED		
OUTLAW AUDIO: LFM-1 EX: 18hz			CERTIFIED		
OUTLAW AUDIO: LFM-1 EX: 25hz			CERTIFIED		
PARADIGM SIGNATURE SUB 2				CERTIFIED	
POWERSOUND: XV-15			CERTIFIED		
PREMIER ACOUSTICS: PA-150		CERTIFIED			
RBH SOUND: SX-12			CERTIFIED		
RBH SOUND: SX-1212R				CERTIFIED	
RYTHMIK AUDIO: FV15HP: 1 PORT MODE				CERTIFIED	
RYTHMIK AUDIO: FV15HP: 2 PORTS MODE				CERTIFIED	
SVS PB12-NSD			CERTIFIED		
SVS: PB13-ULTRA: 15HZ MODE				CERTIFIED	
SVS: PB13-ULTRA: 20HZ MODE				CERTIFIED	
SVS: PB13-ULTRA: SEALED MODE			CERTIFIED		
SVS SB13-ULTRA			CERTIFIED		
SVS SB12-NSD		CERTIFIED			
VELODYNE EQ-MAX 15		CERTIFIED			
VELODYNE: DD18+				CERTIFIED	
XTZ SOUND 3X12				CERTIFIED	
Aperion Audio: Bravus 10D	CERTIFIED				
Axiom Audio: EP400v3	CERTIFIED				
Axiom Audio: EP500v1		CERTIFIED			
Axiom Audio: EP600v1		CERTIFIED			
Emotiva: Xref-10	CERTIFIED				
Emotiva: Ultra 12	CERTIFIED				
EMPtEK ES1010i					
Funkywaves: FW 12.X			CERTIFIED		
JL Audio: f110		CERTIFIED			
Lava: LSP12	CERTIFIED				
RBH S-10	CERTIFIED				
RBH SX-10/R		CERTIFIED			
SVS: PB12-Plus DSP			CERTIFIED		
Velodyne: DD-15		CERTIFIED			
Velodyne: DD-15+			CERTIFIED		
Velodyne: DD-18			CERTIFIED		

# CEA2010 VERSUS MAX SWEEP LEVEL COMPARISON

VALUES ARE THE AMOUNT THAT CEA2010 PASSING RESULTS RECORDED COMPARED TO DURING THE MAXIMUM LEVEL LONG TERM SWEEP  
 POSITIVE VALUES INDICATE HIGHER OUTPUT WITH CEA2010 / NEGATIVE VALUES INDICATE LESS OUTPUT RECORDED VIA CEA2010

Copyright© Audioholics.com / Josh Ricci 2015

MANUFACTURER & MODEL	CENTER FREQUENCY											
	10hz	12.5hz	16hz	20hz	25hz	31.5hz	40hz	50hz	63hz	80hz	100hz	125hz
APERION: BRAVUS II 12D	/	/	/	-3.1	2.8	3.2	6.1	8.0	10.6	8.8	7.8	7.5
BIC ACOUSTECH: PL-200	/	/	/	-3.1	1.1	0.6	1.4	2.8	4.4	4.6	4.5	6
B&W: ASW-610XP	/	/	/	-3.7	-2.8	-0.6	0.8	1.8	3.2	4.1	2.6	3.6
BIC ACOUSTECH: PL-200	/	/	/	-3.1	1.1	0.6	1.4	2.8	4.4	4.6	4.5	6
CADENCE CSX-15 MKII	/	/	/	-4.7	-2.7	-3.2	-3.2	2.5	2.2	1.2	3.3	3.4
ELEMENTAL DESIGNS: A7S-450	/	-1.2	-4.3	-2.5	-0.2	0.6	1	1.4	2.2	2.4	2.4	1.5
EMOTIVA: X-REF12	/	/	/	-2.3	-4.8	-0.6	0.1	3.0	4.5	6.5	6.7	7.9
EPIK: EMPIRE	-1.5	5.4	-0.3	0.1	-0.2	0.4	2.4	3.7	4.1	4.3	5.1	4.8
FUNK AUDIO: 18.0	0.5	0.4	1	0.5	0.8	0.8	0.2	0.4	3.6	4.4	4.7	4.8
HSU: VTF-15H SEALED, EQ1	/	-2	-3.1	-2.8	-1.7	0	0.8	0.7	2.2	1.6	2.3	2.9
HSU: VTF-15H 1 PORTS, EQ1	/	0.4	-0.1	-0.3	-0.2	0.3	0.6	0.4	1.8	1.1	2	2.4
HSU: VTF-15H 2 PORTS, EQ2	/	/	-1.6	2.1	0.3	0.3	0.1	0.3	2.1	1.4	2	2.7
JL AUDIO: E110	/	/	-0.7	0	0.8	1.8	1.5	3.2	6.4	6.2	6.3	6.5
JL AUDIO: E112	/	-1.2	-1.5	0	1.3	1.8	3.6	6.7	8.4	6.5	5.6	6.1
KLIPSCH: SW-311	/	/	/	11.1	4.0	2.8	3.5	4.7	4.7	4.2	2.2	3.1
MARTIN LOGAN: DYNAMO 1500X	/	2.3	-0.4	0.7	0.4	-0.2	0.2	-0.4	2.2	2.5	2.4	1.8
OUTLAW AUDIO: LFM-1 EX: 18hz	/	/	0.5	0.3	1.7	2.5	2.8	2.6	2.0	2.8	2.9	4.5
OUTLAW AUDIO: LFM-1 EX: 25hz	/	/	-2.1	1.5	0.8	1.5	1.7	1.9	1.7	2.6	2.1	3.4
PARADIGM SIGNATURE SUB 2	-1.6	-0.9	-0.3	1.4	3.0	4.1	6.3	8.6	10.9	11.0	9.6	8.1
POWERSOUND: XV-15	/	/	-0.4	1.3	2.5	3.2	4.5	5.1	3.5	2.3	3.0	2.5
PREMIER ACOUSTICS: PA-150	/	/	/	-1.6	-0.8	2.0	2.0	2.3	2.0	2.9	3.4	2.6
RBH SOUND: SX-12	/	/	/	-3.4	-0.7	2.2	1.9	2.9	3.9	3.5	3.3	4.5
RYTHMIK AUDIO: FV15HP: 1 PORT MODE	/	0.7	0.0	0.7	0.9	2.9	5.2	4.6	4.9	6.9	10.3	11.9
RYTHMIK AUDIO: FV15HP: 2 PORTS MODE	/	4.3	1.2	1.2	1.0	2.3	4.7	3.2	3.2	4.6	7.9	9.4
SVS PB12-NSD	/	/	2.3	3.8	0.7	0.7	1.2	1.1	1.2	1.5	1.7	1.4
SVS: PB13-ULTRA: 15HZ MODE	/	-3.2	0.3	1.3	1.7	1.4	1.6	3.4	3.0	3.8	3.7	4.8
SVS: PB13-ULTRA: 20HZ MODE	/	/	-2.1	1.3	1.6	2.1	1.6	2.7	3.3	4.1	4.2	5.1
SVS: PB13-ULTRA: SEALED MODE	/	-6.8	-4.9	-2.6	-0.6	0.5	1.4	4.1	3.3	4.1	4.2	5.2
SVS SB12-NSD	/	1.7	0.4	-0.1	0.0	1.0	1.1	1.0	0.5	0.6	0.9	1.2
VELODYNE EQ-MAX 15	/	/	/	-6.9	-2.4	1.4	2.2	1.8	3.0	3.1	2.6	2.0
VELODYNE: DD18+ SERVO GAIN 1	-4.6	-5.4	-0.7	0.1	0.5	0.0	-0.3	3.2	4.5	4.8	4.7	5.7
VELODYNE: DD18+ SERVO GAIN 8	-3.0	-1.0	-0.2	0.8	0.9	1.3	1.7	2.2	2.2	1.7	1.0	0.8
XTZ SOUND 3X12	/	5.0	4.6	3.9	2.8	2.5	3.3	3.8	4.2	4.3	5.0	5.1
TOTAL RANGE OF VARIATION ALL UNITS / SPL dB	5.1	12.2	9.5	18.0	8.8	7.3	9.5	9.0	10.4	10.4	9.4	11.1
AVERAGE RANGE OF VARIATION ALL UNITS / SPL dB	-2.0	-0.1	-0.5	-0.2	0.4	1.2	1.9	2.9	3.8	3.9	4.1	4.5
TOTAL AVERAGE VARIATION ALL UNITS / ALL FREQS	2.1											
LEAST GAIN OR MOST LOSS												
MOST GAIN OR LEAST LOSS												